



**ModWright Instruments**  
Elegance. Simplicity. Truth.

## PRESS RELEASE

ModWright Instruments, Inc.  
21919 NE 399<sup>th</sup> Street  
Amboy, WA 98601, USA  
[www.modwright.com](http://www.modwright.com)

### LS 300 Balanced Tube Preamplifier

*Presenting the new LS 300 Balanced Tube Preamplifier, featuring outboard supply and dual mono construction. The LS 300 represents our new Fully Balanced Reference Tube preamplifier.*

**Oct. 30, 2018** – ModWright Instruments, Inc., manufacturer of the award winning **KWA 150SE** amplifier, **PH 150** Reference Tube phono stage and **KWI 200** SS integrated amplifier, is introducing the new **LS 300** Balanced tube preamplifier at **2018 CAF**. The LS 300 sets a new standard for Reference, Balanced, Dual Mono tube preamplifiers!

Styled like the PH 150 and KWA 150SE, the LS 300 represents elegant and refined aesthetics and sonics. Multiple sets of fully balanced XLR inputs and outputs as well as RCA inputs and main outs, allow maximum flexibility for any high end system. All RCA inputs are converted to fully balanced signal via high quality Lundahl signal transformers.

The dual mono design of the LS 300, combined with its extremely low noise floor, provide exceptional soundstage and separation. The use of an external power supply and fully separately regulated power supplies per channel are keys to this achievement.

The **LS 300** uses (2) 6922 tube drivers and (2) 5R4GY tube rectifiers, to provide a tonal balance that is both bold and refined, dynamic and musical. The design goal for the LS 300 was to provide the beauty of tubes, whilst maintaining a neutral sonic signature. The 3-dimensionality of tubes is celebrated, along with controlled bass and refined highs.

The back panel features (3) sets of RCA inputs and (2) sets of fully balanced XLR inputs. Main outputs include two sets of RCA single ended outs and two sets of fully balanced XLR outs. One set of RCA inputs also serves as Home Theater Bypass (HT/BP).

Remote control functions include volume, mute and phase invert.

Dimensions: Preamp = 17"W x 12.5"D x 8"H (including tubes) ; Power Supply = 8"W x 10"D x 4.5"H.

The new ModWright LS 300 tube phono stage will be on active display at 2018 CAF, room 312, at the Hilton Washington DC/Rockville Hotel. November 2-4, 2018.

###

**ModWright Instruments, Inc.** is based in Amboy, Washington, and was founded in 2000 by Daniel Wright. The LS 300 Balanced Tube Preamplifier continues a tradition of designing high performance audio equipment, proudly Hand Crafted in the U.S.A. For more information, visit their website at [www.modwright.com](http://www.modwright.com).

**If you would like more information about this topic, please contact**

**Daniel Wright, CEO**

Tel: +1.360.247.6688

E-mail: [modwright@yahoo.com](mailto:modwright@yahoo.com)

**Kristin Boyd, Vice President**

Tel: +1.360.247.6688

E-mail: [kristin.modwright@yahoo.com](mailto:kristin.modwright@yahoo.com)